



3V0-42.20^{Q&As}

Advanced Design VMware NSX-T Data Center

Pass VMware 3V0-42.20 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/3v0-42-20.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

An architect is helping an organization with the Physical Design of an NSX-T Data Center solution.

This information was gathered during a workshop:

Some workloads should be moved to a Cloud Provider.

Extend network's VLAN or VNI across sites on the same broadcast domain.

Enable VM mobility use cases such as migration and disaster recovery without IP address changes.

Support 1500 byte MTU between sites.

Which selection should the architect include in their design? (Choose the best answer.)

- A. Load Balancer
- B. Reflexive NAT
- C. SSL VPN
- D. L2 VPN

Correct Answer: D

QUESTION 2

Which three assessment findings are part of a Conceptual Design? (Choose three.)

- A. risks
- B. host names
- C. justifications
- D. constraints
- E. assumptions
- F. vendor model

Correct Answer: ACD

QUESTION 3

An architect is helping an organization with the Logical Design of an NSX-T Data Center solution.

This information was gathered during the Assessment Phase:



There is a performance based SLA for East – West traffic.

The business critical applications require prioritization of their traffic.

One of the services is a file share and has a high demand for bandwidth.

Which selection should the architect include in their design? (Choose the best answer.)

- A. Review average North/South traffic from the core switches and firewall.
- B. Include a segment QoS profile and review the impact of utilizing this feature.
- C. Meet with the organization's application team to get additional information.
- D. Monitor East-West traffic throughout normal business cycles.

Correct Answer: B

QUESTION 4

Which selection must be taken into consideration when creating a Logical Design for a planned migration? (Choose the best answer.)

- A. An N-VDS can only attach to a single Overlay transport zone.
- B. An N-VDS can only attach to a single VLAN transport zone.
- C. An N-VDS can attach to both an Overlay and a VLAN transport zone to a N-VDS having different name/s.
- D. An N-VDS must be disabled before attaching both Overlay and VLAN transport zones.

Correct Answer: B

QUESTION 5

An architect is helping an organization with the Physical Design of an NSX-T Data Center solution.

This information was gathered during the Assessment Phase:

There is a critical application used by the Finance Team.

The critical application has an availability and recoverability SLA of 99.999%.

The critical application is sensitive to network changes.

Which two selections should an architect include in their design? (Choose two.)

- A. Configure Tier-0 gateway for eBGP and ECMP.
- B. Configure Tier-1 gateway for eBGP and ECMP.



- C. Enable BFD on Tier-0 gateway.
- D. Install and configure hosts with 100Gbps physical NICs.
- E. Configure multiple static routes on Tier-1 gateway.

Correct Answer: BD

[Latest 3V0-42.20 Dumps](#)

[3V0-42.20 Practice Test](#)

[3V0-42.20 Study Guide](#)