



DEA-5TT1^{Q&As}

Associate - Networking Exam

Pass EMC DEA-5TT1 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/dea-5tt1.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

On which OSI layers do standard ACL filters operate?

- A. 2 and 3
- B. 2 and 7
- C. 3 and 4
- D. 4 and 7

Correct Answer: C

QUESTION 2

DRAG DROP

What is the correct sequence of steps that occur in the communications between the client and server to obtain an IP address from a DHCP server?

Select and Place:

DHCP client sends a DHCPREQUEST message to accept the IP address	Step 1
DHCP client sends a DHCPDISCOVER message to request an IP address	Step 2
A DHCPACK message is sent by the DHCP server to the DHCP client to acknowledge that the client has accepted the offered IP address	Step 3
DHCP server receives the DHCPDISCOVER message	Step 4
DHCP server offers an available IP address by sending a DHCPPOFFER message to the DHCP client	Step 5

Correct Answer:



DHCP client sends a DHCPDISCOVER message to request an IP address

DHCP server receives the DHCPDISCOVER message

DHCP server offers an available IP address by sending a DHCP OFFER message to the DHCP client

DHCP client sends a DHCPREQUEST message to accept the IP address

A DHCPACK message is sent by the DHCP server to the DHCP client to acknowledge that the client has accepted the offered IP address

QUESTION 3

What is the default OSPF "hello interval"?

- A. 5 seconds
- B. 10 seconds
- C. 15 seconds
- D. 30 seconds

Correct Answer: B

QUESTION 4

Which fields are mandatory TLVs in a LLDP PDU frame?

- A. System Capabilities and Management Address
- B. Chassis ID, Port ID, and Time-to-Live
- C. IP Address, Default Gateway, and DNS
- D. Port Description, System Name, and System Description

Correct Answer: B

Reference: https://en.wikipedia.org/wiki/Link_Layer_Discovery_Protocol#:~:text=Each%20LLDP%20frame%20starts%20with,and%20length%20fields%20are%20

QUESTION 5

A network administrator is troubleshooting an OSPF routing issue. There are two paths to a destination network from



one switch. In addition, one path is comprised of four 1 Gb links. The other path is comprised of two 1 Gb and two 100 Mb links. The administrator ran several trace routes and notices that the packets are swapping back and forth between the two paths.

Which corrective action must be taken on the switch infrastructure to correct this issue?

- A. Manually specify the OSPF Router ID on each switch within the path.
- B. Break the paths into multiple OSPF areas.
- C. Change the reference speed used by OSPF in cost calculations on all switches within the path.
- D. Switch all routing protocols to RIPv2.

Correct Answer: C

[Latest DEA-5TT1 Dumps](#)

[DEA-5TT1 Study Guide](#)

[DEA-5TT1 Exam Questions](#)