



DES-4421^{Q&As}

Specialist - Implementation Engineer, PowerEdge MX Modular Exam

Pass EMC DES-4421 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/des-4421.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What configuration is supported for a fully populated MX740c compute sled?

- A. 1 Fabric B mezz card 1 Fabric C mezz card with Fabric A being integrated into the system board
- B. 1 Fabric A mezz card 1 Fabric B mezz card with Fabric C being integrated into the system board
- C. 2 Fabric A mezz cards 2 Fabric B mezz cards 2 Fabric C mini-mezz cards
- D. 1 Fabric A mezz card 1 Fabric B mezz card 1 Fabric C mini-mezz card

Correct Answer: D

Reference: https://i.dell.com/sites/csdocuments/Product_Docs/en/poweredge-mx740c-technical-guide.pdf?newtab=true (p.9)

QUESTION 2

In an MX7000, which components are cooled by the rear fans?

- A. Fabric A, B, and C IOMs only
- B. All compute and storage sleds
- C. Management Modules only
- D. Fabric A, B, and C IOMs and the Management Modules

Correct Answer: D

Reference: <http://bladesmadesimple.com/2018/08/a-first-look-at-the-dell-emc-poweredge-mx/>

QUESTION 3

A technician has replaced an MX chassis tub. They complete the tub installation and power on the chassis. They notice that the KVM is no longer functional. What should the technician do after confirming the KVM feature is still enabled in OME-M?

- A. Ensure all cables connecting the tub to the left ear control panel are connected properly
- B. Ensure all power supplies are connected and powered-on
- C. Ensure all cables connecting the tub to the right ear control panel are connected properly
- D. Ensure all installed Management Modules are connected to the network

Correct Answer: A



QUESTION 4

Which I/O module is supported for Fabric B?

- A. MX5016s
- B. MSG610s
- C. MX5000s
- D. MX5108n

Correct Answer: D

Reference: <https://hasanmansur.com/2019/01/08/mx7000-networking-part-1-introduction-components/>

QUESTION 5

Where is a valid storage location for extracting the full MX7000 chassis logs package?

- A. VMFS
- B. FTP
- C. CIFS
- D. CSV

Correct Answer: C

Reference: https://www.dell.com/support/manuals/us/en/04/poweredge-mx7000/omem1.00.01_ug/sas-iom-overview?guid=guid-35fc46f8-41b1-4b9f-9aa9-037e400ec3f6andlang=en-us

[Latest DES-4421 Dumps](#)

[DES-4421 PDF Dumps](#)

[DES-4421 Practice Test](#)