



# DES-5121<sup>Q&As</sup>

Specialist - Implementation Engineer - Campus Networking Exam

**Pass EMC DES-5121 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/des-5121.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

A network has two switches with the following IP addresses:

Switch1: 192.168.1.240

Switch2: 192.168.1.241

The administrator wants to add VRRP on an existing switch configuration using the virtual IP 192.168.1.240.

What is a VRRP requirement for this configuration?

- A. Priority 241 on Switch2
- B. Priority 255 on Switch1
- C. Virtual Router ID 1
- D. Virtual Router ID 240

Correct Answer: B

---

### QUESTION 2

Which function does a VRRP backup router perform?

- A. Sends keepalive advertisements to the other backup routers
- B. Processes and responds to ARP requests
- C. Forwards packets to the Master with a destination IP of the virtual IP address
- D. Receives packets with the virtual MAC address as the destination for other backup routers

Correct Answer: D

---

### QUESTION 3

When configuring a PBR route-map, what are the configurable "SET" options?

- A. set ip source, set ip next-hop, and set ip default next-hop
- B. set ip next-hop, set ip source, and set ip precedence
- C. set ip next-hop, set ip default next-hop, and set ip precedence
- D. set ip source, set ip default next-hop and set ip precedence

Correct Answer: C

---



#### QUESTION 4

Which default security level can be assigned to limit access of a specific user to a Dell EMC N-Series switch?

- A. Level 0
- B. Level 1
- C. Level 5
- D. Level 15

Correct Answer: A

Reference: [https://www.dell.com/support/manuals/us/en/04/force10-s4048-on/s4048\\_on\\_9.9.0.0\\_config\\_pub-v1/configuring-privilege-levels?guid=guid-2fa480e0-1660-41d8-8ac2-45aa90d5bb71andlang=en-us](https://www.dell.com/support/manuals/us/en/04/force10-s4048-on/s4048_on_9.9.0.0_config_pub-v1/configuring-privilege-levels?guid=guid-2fa480e0-1660-41d8-8ac2-45aa90d5bb71andlang=en-us)

---

#### QUESTION 5

After setting up the VoIP configuration, a network administrator issues the following commands with the results shown:

```
console# show voice vlan Administrative Mode.....Enable
```

```
console# show voice vlan it gi 1/0/2
```

```
Interface.....Gi1/0/2
```

```
Voice VLAN Interface Mode.....Enabled
```

```
Voice VLAN ID.....10
```

```
Voice VLAN COS Overwrite.....False
```

```
Voice VLAN DSCP Value.....46
```

```
Voice VLAN Port Status.....Enabled
```

```
Voice VLAN Authentication.....Disabled
```

Based on this information, what is the Layer 3 QoS value?

- A. 5
- B. 10
- C. 46
- D. Gi1/0/2

Correct Answer: C